co-ax® Valve Specification Sheet

| INSTRUCTIONS: To begin data entry, click in Company: field. Tab to advance fields. Simply click in appropriate checkboxes. | | ess: /Zip: | | | | Date: OEM Reseller End User |
|--|---------------------|------------------------|--|----------|-----------------|--------------------------------|
| | E-Ma | il: | | | | |
| Function: | Design: | Actuation | on: | Voltage: | Certifications: | Other: |
| Normally Closed | · | | olenoid) | 24 V DC | Ex Zone 1 | |
| Normally Open | 3/2 Way | Externally (air) | | 110 V AC | Ex Zone 2 | |
| | Modular | Externally (hydraulic) | | Other | CSA/UL | |
| Port Connections: | | | | | | |
| Threaded Size | eaded Size Fl | | | | | |
| NPT | | ANS | | | _ | |
| SSPP | D | | | | _ | |
| SAE | Of | | | | _ | |
| Other | | _ | | | | |
| Construction Material | s: | | | | | |
| Brass | Nickel Plated Brass | | | m | | |
| Ivanized Steel Nickel Plated Steel | | ed Steel | Stainless Steel Other: | | | |
| Electrical Connection: | } | | | | | |
| DIN Connector | Metal Terminal Box | | 1/2 Conduit Connector Other: | | | |
| Options: | | | | | | |
| Nounting Brackets Position Indicators | | licators | (Please describe quantity for position indicators and desired indication below under Comm | | | |
| Application Details: | | | | | | |
| Media: | | | | | | |
| Media Temperature: | | | Abrasive: YE | S NO | Specific G | ravity: |
| Ambient Temperature: | | | | | - 1 | , |
| Flow Rate: | | | Pressure Rand | ge: | | |
| Cv Required: | | | Back Pressure: | | | |
| Maximum allowable P-Δ: | | | Vacuum: | | | |
| Switching Frequency: | | | Required Switching Time: | | | |
| Quantity: | | | 4 | J =: | | |
| Application Description | nn• | | | | | |
| application Description | J11. | If NO, pleas | | | | |

Price Performance Other

Comments:

